



Zoll-Umrechnungstabelle

Gewindedurchmesser Zoll	mm	Gewindegänge auf 1"		Gewindegänge auf 1"	
		UNC	UNF	BSW (Ww)	BSF
No. 0	1.524		80		
No. 1	1.854	64	72		
No. 2	2.184	56	64		
No. 3	2.515	48	56		
No. 4	2.845	40	48		
No. 5	3.175	40	44		
No. 6	3.505	32	40		
No. 8	4.166	32	36		
No. 10	4.826	24	32		
No. 12	5.486	24	28		
1/4"	6.350	20	28	20	26
5/16"	7.938	18	24	18	22
3/8"	9.525	16	24	16	20
7/16"	11.112	14	20	14	18
1/2"	12.700	13	20	12	16
9/16"	14.288	12	18	12	16
5/8"	15.875	11	18	11	14
3/4"	19.050	10	16	10	12
7/8"	22.225	9	14	9	11
1"	25.400	8	12	8	10
1 1/8"	28.575	7	12	7	9
1 1/4"	31.750	7	12	7	9
1 3/8"	34.925	6	12	6	8
1 1/2"	38.100	6		6	8
1 3/4"	44.450	5		5	7
2"	50.800	4 1/2		4 1/2	7

Amerikanische Gewinde mit 60° Flankenwinkel:

UNC = unified coarse (Grobgewinde)

UNF = unified fine (Feingewinde)

Britische Gewinde mit 55° Flankenwinkel:

BSW (Ww) = British Standard Whitworth (Grobgewinde)

BSF = British Standard Fine (Feingewinde)

Gewindebestimmung einer Zollschaube:

